

- Proven Wertheim quality
- Resistance grade II
- Certified fire protection

Privately insurable up to EUR 100.000

Commercial insurable

up to EUR 50.000

see page 7



EN1143-1 Burglary protection



Grade II



Grade II + LFS30



Vsć

Class EN 2

Product Information

Door Hinge

DIN right - standard optional: DIN left

Door Opening Angle

180°

Body

Double-walled design, filled with reinforced, highly resistant filler and heat-absorbing materials

Door Structure

Designed with double rebate and three walls, filled with reinforced, highly resistant filler and heatabsorbing materials, internal transom space with partially attached drill protection, door rebate with several fire and smoke protection seals

Locking

Driven on three sides by solid steel bolts via a boltwork with a base plate, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring see page 61

Prepared for floor and rear wall bolting connection, anchoring material included in the scope of delivery

Cable Hole

Door hinge side, rear wall bottom

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037

optional: paint finish according to RAL

Locks see page 56

Key lock VdS class 1, Wittkopp 2648, 2 keys (145 mm)
Electronic lock VdS class 2.

Wittkopp Primor 2600 optional: other lock models (main locks or possible additional locks)

Interior see page 54 Adjustable shelf

optional: additional shelf, inside locker,

drawer, pull-out shelf

Accessories see page 59 Optional: IAS switch set, interior lighting



Model Overview

BP Series

